

VC60D+ New Type Digital Insulation Tester

Basic Function	Range	Basic accuracy
		VC60D+
Measuring voltage	1000V/2500V	±10%
Median resistance	<4mA	√
Median voltage	200MΩ:6-199.9MΩ	±(5%±5bit)
	2GΩ:0.06-1.999GΩ	±(5%±5bit)
1000V	20GΩ:0.6-19.99GΩ	±(5%±5bit)
Voltage test	200MΩ:5-199.9MΩ	±(5%±5bit)
	2GΩ:0.05-1.999GΩ	±(5%±5bit)
2500V	20GΩ:0.5-19.99GΩ	±(5%±5bit)
Measuring Voltage	AC750V	± (1% +6bit)
Jack position	Insulation resistance: L、E AC750V : ACV G AC750V: ACV G	
Overload Indication	√	
Auto power off	√	
Max. display	1999	
Product Dimension	175×110×70mm	
Product Net Weight	Approx. 720g (include battery)	
Power	5# battery LR6 (1.5) ×8	
Using Temperature	0℃~40℃	
Relative Humidity	30%RH~85%RH	
Special Function	VC60D+	
Low Battery Indication	√	
Alarm Function	Red indicator light is illuminated	
Unit Symbol Display	√	
Over Range Display	“1”	